

## RAM

SWING GATES ACTUATOR  
VERSIONS 230V AND 24V

Life  
made  
easy




# RAM

Technical features



### DIMENSIONS (mm)



### TECHNICAL CHARACTERISTICS

	RAM 220 24V	RAM 300 24V	RAM 300 230V	RAM 500 24V	RAM 500 230V
Voltage	24 VDC	24 VDC	230 VAC	24 VDC	230 VAC
Power consumption	60 W	100 W	280 W	100 W	280 W
Max. absorption	3 A	5 A	1,2 A	5 A	1,2 A
Max. thrust	1500 N	2000 N	1800 N	1800 N	2000 N
Standard stroke	374 mm	374 mm	374 mm	524 mm	524 mm
Duty cycle	Intensive use	Intensive use	40%	Intensive use	30%
Protection degree (IP)	IP44	IP44	IP44	IP44	IP44
Insulation class	2	2	1 (earthing)	2	1 (earthing)
Working temperature	-20°C / +50°C	-20°C / +50°C	-20°C / +50°C	-20°C / +50°C	-20°C / +50°C
No-load speed	18 mm/s	21 mm/s	16 mm/s	22 mm/s	15 mm/s
Weight	7 kg	7,8 kg	8,3 kg	8,8 kg	9,3 kg



OFFICIAL DEALER:

 **COMUNELLO**  
**AUTOMATION**

AUTOMATION FOR GATES, DOORS AND BARRIERS

FRATELLI COMUNELLO S.P.A.

HEADQUARTERS

Via Zarpellon, 33

36027 San Giuseppe di Cassola, Vicenza, Italy

Tel. +39 0424 585111 Fax +39 0424 533417

info@comunello.it www.comunello.com

REGISTERED OFFICE

Via Cassola,64 - C.P.79

36027 Rosà, Vicenza, Italy

Tel. +39 0424 585111 Fax +39 0424 533417

info@comunello.it www.comunello.com